



360 G. P. H. (1363 L. P. H.)

The Rule 360 provides outstanding quality and value. It is economically priced and designed for small boats. 3/4" (19mm) discharge outlet. 12 volts DC unless noted.

- NON-AUTOMATIC
- Model 24 360 GPH (1363 LPH)
 - Model 24-6 360 GPH (1363 LPH) with 6' (1.8m) wire leads
 - Model 24/35 360 GPH (1363 LPH) Pump with Rule-A-Matic Float Switch



500 G. P. H (1893 L. P. H.)

The Rule 500 offers many design features while keeping size and cost to a minimum. Especially popular on smaller craft, Rule 500 pumps are unmatched in pumping power and longevity. 3/4" (19mm) discharge outlet. 12 volts DC unless noted.

- RULE-MATE
- Model RM500 500 GPH (1893 LPH) Rule-Mate
 - Model RM500-24 500 GPH (1893 LPH) Rule-Mate (24 volt)

- AUTOMATIC
- Model 25S 500 GPH (1893 LPH) Automatic
 - Model 25S-24 500 GPH (1893 LPH) Automatic (24 volt)
 - Model 25S-6 500 GPH (1893 LPH) Automatic with 6' (1.8m) leads



- NON-AUTOMATIC
- Model 25D 500 GPH (1893 LPH)
 - Model 25DC 500 GPH Cartridge (1893 LPH)
 - Model 25D-6 500 GPH (1893 LPH) with 6' (1.8m) leads
 - Model 25-40 500 GPH (1893 LPH) with Rule-A-Matic Plus Float Switch
 - Model 26D 500 GPH (1893 LPH) (24 volt)



700/750 G. P. H. (2650/2839 L. P. H.)

Rule's 700 and 750 G.P.H. Pumps offer increased capacity in keeping with it's 3/4" (19mm) discharge outlet. 12 volts DC unless noted.

- RULE-MATE
- Model RM750 750 GPH (2839 LPH) Rule-Mate
 - Model RM750-24 750 GPH (2839 LPH) Rule-Mate (24 volt)

- NON-AUTOMATIC
- Model 20RC 700 GPH Cartridge (2650 LPH)